

KNOT WIRE WHEEL BRUSHES

- The individual knot wire tufts of a knot wheel provide minimal flexibility for more aggressive brushing action
- Rugged knot-type construction provides high brush flexibility, more uniform results, maximum safety and efficient operation at high speeds
- Brushes larger than 6" should be mounted on stationary tables; those 6" and smaller can be mounted to stationary installations or attached to portable tools

STANDARD TWIST KNOT

- Aggressive, high impact action for severe application,
- To be used with straight grinders, bench and pedestal grinder or right angle grinder



STRINGER BEAD

- Tighter knot, fit into more recessed area
- To be used with straight grinders or right angle grinder



There are other wheel sizes, wire sizes & arbor sizes available for all brush types.

Different materials are also available.

STRINGER BEAD

- Small width allows this brush to be used in recessed area such as welding junctions
- **Application:** Cleaning stringer bead welds



Model No.	Brush Dia."	Arbor Hole	Wire Gauge"	Trim Length"	Face Width"	Max RPM	Price /Each
STEEL							
BX338	4 7/8	5/8"-11NC	0.02	1	3/16	12000	
BX161	6 1/2	5/8"-11NC	0.02	1 1/4	3/16	12000	
STAINLESS							
BX270	4 7/8	5/8"-11NC	0.02	1	3/16	12000	
BX273	6 1/2	5/8"-11NC	0.02	1 1/4	3/16	12000	

HIGH SPEED STEEL SMALL GRINDER, STRINGER BEAD

- Works aggressively, smoothly and efficiently on air or portable power tools
- **Application:** Bead scale removal



Model No.	Brush Dia."	Arbor Hole	Colour	Wire Gauge"	Trim Length"	Max RPM	Price /Each
STEEL							
BX288	4	5/8"-11NC	Steel	0.02	7/8	20000	
STAINLESS STEEL							
BX311	4	5/8"-11NC	Steel	0.02	7/8	20000	

STANDARD TWIST KNOT WITH 1/4" SHANK

- Designed to operate at high speeds
- **Applications:** Maintenance and metal surface cleaning



Model No.	Brush Dia."	Wire Gauge"	Trim Length"	Max RPM	Price /Each
STEEL					
BX193	3	0.014	5/8	25000	
BX196	4	0.014	7/8	20000	
STAINLESS					
BX195	3	0.014	5/8	25000	
BX198	4	0.014	7/8	20000	

STANDARD TWIST KNOT

- **Application:** Removal of rubber flash, paint slag, scale, rust, surface contamination, weld cleaning, blending, finishing, deburring, descaling, pipeline cleaning and general cleaning



Model No.	Brush Dia."	Arbor Hole	Wire Gauge"	Trim Length"	Face Width"	Max RPM	Price /Each
STEEL							
BX125	4	3/8"	0.014	7/8	5/16	20000	
BX137	6	5/8"-11NC	0.025	1 1/2	1/2	9000	
BX144	8	5/8"	0.025	1 11/16	5/8	8500	
STAINLESS							
BX202	4	3/8"	0.014	7/8	5/16	20000	
BX272	6	5/8"-11NC	0.025	1 1/2	1/2	9000	

STANDARD TWIST KNOT HIGH SPEED STEEL SMALL GRINDER

- Works aggressively, smoothly and efficiently on air or portable power tools
- **Applications:** Cleans grooves, T-connections, weld beads and surface prep



Model No.	Brush Dia."	Arbor Hole	Colour	Wire Gauge"	Trim Length"	Max RPM	Price /Each
STEEL							
BX305	4	5/8"-11NC	Steel	0.02	7/8	20000	
BX206	5	5/8"-11NC	Steel	0.02	1	12000	
STAINLESS							
BX299	4	5/8"-11NC	Steel	0.02	7/8	20000	
BX207	5	5/8"-11NC	Steel	0.02	1	12000	

WIRE WHEEL BRUSHES

- Narrow face for confined and hard to reach contact areas
- Low flex high impact aggressive brush action
- Perfect for expansion joints and filler welds
- For root and hot pass weld cleaning
- Customization available



FELTON BRUSHES



Model No.	Brush Dia."	Face Width"	Fill Dia."	Arbor Size	Knot Type	No. of Knots	RPM	Price /Each
STEEL								
TT265	4	3/16	0.020	5/8"-11	Stringer	32	20000	
TT271	4-7/8	3/16	0.020	5/8"-11	Stringer	48	12500	
TC019	5-7/8	3/16	0.020	5/8"-11	Stringer	48	12500	
NU438	4	1/2	0.020	5/8"-11	Standard	20	20000	
NU440	6	1/2	0.014	5/8"-11	Standard	28	9000	
NU442	8	5/8	0.014	5/8"-11	Standard	40	6000	
STAINLESS								
TT270	4	3/16	0.020	5/8"-11	Stringer	32	20000	
TT272	4-7/8	3/16	0.020	5/8"-11	Stringer	48	12500	
TT273	5-7/8	3/16	0.020	5/8"-11	Stringer	48	12500	
NU439	4	1/2	0.020	5/8"-11	Standard	20	20000	
NU441	6	1/2	0.014	5/8"-11	Standard	28	9000	
NU443	8	5/8	0.014	5/8"-11	Standard	40	6000	